

GC ULTRA-SHIELD ROOF FLASH

POLYUREA URETHANE LIQUID FLASHING

ULTRA-SHIELD ROOF FLASH is a high viscous, trowel or butter grade enhanced polyurea-urethane formula that can be used in conjunction with a variety of liquid coatings and a variety of roof membranes.

Ultra-Shield Roof Flash is designed to seal roof details, such as seams, penetrations and terminations. Ultra-Shield Roof Flash is environmentally friendly with its low VOC's and fast moisture-cure properties. This high performing polyurea-urethane is durable, reflective and UV resistant and has excellent vertical hang and performs well under ponding water.

RECOMMENDED USES

- Spot repairs over built up spray foam, wood, concrete
- Seam, flashing, and penetration reinforcement for metal and singl-ply systems
- Sealant for solar systems and air conditioning systems

PACKAGING

3-½ gallons pail

COLOR

White and Aluminum

TECHNICAL DATA

PHYSICAL PROPERTIES		
Total Solids by Volume	ASTM D2697	88% ± 2
Total Solids by Weight	ASTM D-2369	92% ± 2
Ultimate Elongation,	ASTM D412	150 ± 50%
Tensile Strength (Die C)	ASTM D412	1500 ± 300 psi
Tear Resistance	ASTM D624	150± 50 psi
Hardness Shore A	ASTM D-2240	60
Specific Gravity		1.35
Viscosity @ 75°F (24°C)		20,000 - 40,000 cps
Low Temperature Flexibility	ASTM D1737	Pass
Abrasion Resistance	ASTM C501	29 Mg Loss
Volatile Organic Compound	ASTM D2369-81	100 gm/liter <0.83 lb/gal

The information contained herein is for purposes of identifying the product and does not constitute a warranty that the product will conform to that description. Product specifications and performance will vary depending on application methodologies, raw materials and other factors.

EQUIPMENT

Roof flash may be applied by brush, spatula or trowel

COVERAGE

The first coat of Ultra-Shield Roof Flash should be applied at the rate of 1 ½ gallon/100 square feet or 150 sqft/gallon. The dry film thickness, exclusive of aggregate is 12 ± 2 mils per coat at rate of 1 ½ gallon/100 sqft or 150 sqft/gallon.

For metal roofs, fasteners coverage count per 3 ½ gal pail is 1400 square feet. For seams, 3 ½ gal pail @ 24 wft, 6" on center will cover 295 linear feet.

MIXING

Before application, mix Ultra-Shield Roof Flash using a mechanical mixer at slow speed. Mix Ultra-Shield Roof Flash thoroughly until a homogenous mixture and color is attained. Do not dilute under any circumstance.

APPLICATION

Prior to coating any surface with Ultra-Shield Roof Flash, be sure the coating will adhere by performing an adhesion test (ASTM D903). Do not apply when temperatures are below 40°F (4.4°C) or when precipitation is in the forecast within 8 hours.

PERSONAL PROTECTIVE EQUIPMENT

Ultra-Shield Roof Flash is a manually installed mastic requiring eye protection and appropriate gloves. It is essential that maximum effort is made to protect the installer and others near the workplace from undue exposure.

JOB-SITE PROTECTION

Ultra-Shield Roof Flash can carry considerable distances and attention should be given to the following:

1. Post warning signs a minimum of 100 feet from the work area.
2. Cover all intake vents near the work area.
3. Minimize or exclude all personnel not directly involved with the spray application.
4. No welding, smoking or open flames.
5. Have CO₂ or other dry chemical fire extinguisher available at the jobsite.
6. Provide adequate ventilation.

STORAGE AND SHELF LIFE

Ultra-Shield Roof Flash has a shelf life of one (1) year from date of manufacture in original, factory-sealed containers when stored indoors at a temperature between 60-95°F (15-35°C). Keep containers closed and store in a dry, cool place away from direct sunlight, heat, sparks, open flame, and moisture.

HEALTH AND SAFETY

GCMC is committed to the health and safety of our customers. GCMC products shall only be installed by certified contractors. Applicators are required to follow all proper handling, safety and installation procedures. Safety Data Sheets (SDS) are available on this product. Any

individual who may come in contact with these products should read and understand the SDS.

VAPOR INHALATION

The best form of protection against organic solvents or potentially sensitizing vapors in the workplace is a fresh air supply. Numerous manufacturers, including the 3M Company and MSA, make full face fresh air masks. For maximum protection, we recommend use of NIOSH/MSHA approved self-contained breathing apparatus with a full-face piece operated in a positive pressure mode. In well-ventilated application conditions, the use of Type C organic vapor cartridge respirators is acceptable. Effects of overexposure to vapor are characterized by nasal and respiratory irritation, dizziness, nausea, headache, fatigue, possible unconsciousness or even asphyxiation. Vapor inhalation problems are characterized by coughing, shortening of breath and tightness in the chest. Anyone exhibiting these types of symptoms should be immediately removed from the workplace and administered oxygen or fresh air. If the condition is prolonged or extreme, SUMMON EMERGENCY TRAINED MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT

To prevent excessive skin contact with the sprayed product, we recommend use of fabric coveralls and neoprene or other resistant gloves. Skin contact with liquid components can result in a rash or other irritation. Wash the affected skin area with water. Wipe residual liquid from the skin with a clean cloth, then wipe the affected area with 30% solution of rubbing alcohol. Follow the alcohol wipe with repeated washings with soap and water. If a rash or other irritation develops, see a physician.

EYE CONTACT

Wear a full-face mask or OSHA-approved protective goggles. Eye Contact with liquid or sprayed components can result in corneal burns or abrasions. Upon exposure, eyes should be flushed with water for an extensive period. SUMMON EMERGENCY TRAINED MEDICAL ATTENTION IMMEDIATELY.

FLAMMABILITY

Flash point 108°F (42°C) for components A and B. Avoid open flame or spark sources. Avoid excessive heat. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors or other ignition sources at locations distant from the material-handling point. Never use a welding or cutting torch on or near the drum. In case of fire, use CO₂, steam, dry chemicals or water fog.

TECHNICAL SERVICES

Additional information, such as brochures, technical assistance, and other management services are also available from a General Coatings Manufacturing Corp. Technical Consultant.

GC ULTRA-SHIELD ROOF FLASH

POLYUREA URETHANE LIQUID FLASHING

LIMITED WARRANTY. We warrant our Products to be free of manufacturing defects and to comply with the Product's current published physical properties when tested under controlled conditions. Our sole responsibility is limited to replacement of that portion of any Products found to be defective at the time of manufacture. There are no other warranties of any nature whatsoever, whether expressed or implied, including an express disclaimer of any warranty of merchantability or fitness for a particular purpose. Further, we disclaim any liability for damages of any type, however caused, including remote, consequential damages, or special damages resulting from any theory of liability, whether based on tort, negligence, or strict liability. We disclaim responsibility for any claims of intellectual property infringement through use of our Products in any manner. Where Products are used as a waterproofing membrane or floor coating, no warranty or guarantee is issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, abnormal wear and tear, or improper application by the applicator. Damage caused by abuse, neglect, lack of proper maintenance, acts of nature and/or physical movement of the substrate or structural defects are also excluded. In all instances and as a pre-condition to any available remedy, we reserve the right to conduct sample testing and performance analysis on any materials claimed to be defective, performed prior to any repairs being made by owner, general contractor, or applicator. Our limited warranty is void if repairs have been made or attempted, or if the claimed defect has been adulterated prior to our ability to conduct a formal investigative analysis.

DISCLAIMER: Please read all information in the general guidelines, technical data sheets, application guide and safety data sheets (SDS) before applying material. Products are for professional use only and should only be applied by professionals who have prior experience with our Products or have undergone specific training in their proper application. Published technical data and instructions are subject to change without notice. Contact your local representative or visit our website for current technical data and instructions. All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of these tests are not guaranteed and are not to be construed as a warranty, either expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with any product. It is the user's responsibility to satisfy himself, by his own information and tests, to determine suitability of the product for his own intended use, application and job situation and user assumes all risk and liability resulting from his own use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones that may exist. We are not liable to the purchaser, end-user, or any third party for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, our Products. Recommendations or statements, whether verbal or in writing, shall not be binding upon us unless in writing and signed by one of our authorized corporate officers. Technical and application information is provided for establishing a general profile of the material and proper application procedures. Test performance results were obtained in a controlled environment and we make no claim that these tests or any other tests, accurately represent all environments. We are not responsible for typographical errors. © General Coatings Manufacturing Corporation. All Rights Reserved. Revision ULTRA-SHIELD ROOF FLASH_08172020EA