

AIM HIGHER WITH UPC

Closed-Cell HFO Spray Foam

WHY UPC CLOSED-CELL HFO SPRAY FOAM?

UPC closed-cell spray foam insulation outperforms traditional insulation as an efficient barrier against air, moisture, and vapor in just one application. This innovative insulation adheres to a variety of surfaces and expands to establish a continuous, impermeable building envelope.

Our original closed-cell spray foams also offer applicators and distributors low GWP options without compromising quality.

Benefits include:

- Air Barrier
- Custom-Fit Insulation
- Vapor Barrier
- Indoor Air Quality
- Improved Structural Integrity
- Seamless
- Sustainable R-Value



SPRAY FOAM BENEFITS YOU CAN TRUST

- ✓ Enhanced Energy Efficiency
- ✓ Versatile Application
- ✓ Environmentally Friendly



Scan Me!

UPC 2.0™ HFO

LOW GWP CLOSED-CELL

Ultra-low global warming potential closed-cell foam meeting the strictest regulatory and environmental standards. Leading formulation with incredible sprayability. Designed for single pass thickness up to 3.0".

- R-value of 7.6 @ 1"
- Yield up to 4,700 Board Feet
- Available in Regular, Summer and Winter Grades
- HFO 1233zd Technology
- Contains no CFCs or HCFCs
- Appendix X Approved
- Intertek CCRR
- Intertek Clean-Air Gold Certified

UPC 2.0™ HFO MAX

HIGH-YIELD LOW GWP CLOSED-CELL

This low global warming potential closed-cell foam meets the strictest regulatory and environmental standards. Leading formulation with maximum board per square foot coverage. Designed for single pass thickness up to 3.0".

- R-value of 7.9 @ 1"
- Yield up to 5,000 Board Feet
- Available in Regular, Summer and Winter Grades
- HFO 1233zd Technology
- Contains no CFCs or HCFCs
- Appendix X Approved
- Intertek CCRR
- Intertek Clean-Air Gold Certified

UPC 2.0™ HIGH-LIFT HFO

HIGH-LIFT CLOSED-CELL

This closed-cell foam is designed for decreased labor costs. Formulated with HFO blowing agent with a global warming potential (GWP) of 1. Designed for single pass thickness up to 4.0".

- R-Value of 7.9 @ 1"
- Yield up to 5,000 Board Feet
- Available in Regular, Summer and Winter Grades
- Contains no CFCs or HCFCs
- Appendix X Approved
- Intertek CCRR
- Intertek Clean-Air Gold Certified

Made in America under the ISO 9001 Quality Assurance Program.

DISCLAIMER: Please read all information in the technical data sheets, application guides and safety data sheets (SDS) before installing UPC products. UPC products are for professional use only and applied by professionals who have undergone training in the application of UPC products. Published technical data and instructions are subject to change without notice. Contact your local UPC representative or visit us on the web at www.upcfoam.com for current technical data and instructions. All guidelines, recommendations, statements, and technical data contained herein are based on information and tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. It is the user's responsibility to satisfy himself, by his own information and tests, to determine suitability of the product for his own intended use, application and job situation. User assumes all risk and liability resulting from his own use of the product. Neither seller nor manufacturer shall be liable to the buyer or any third party for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product.



We aim *higher*, aim *better* and our products go *further*.

UPCFOAM.COM | (682) 503-8069 | UPC@UPCFOAM.COM
3001 E. PIONEER PARKWAY, ARLINGTON, TX 76010