



INSULATION CERTIFICATE

This form must be filled out and posted to comply with building code requirements. Meets IRC Chapter 11 Energy Efficiency Requirements and IECC Chapter 4, Commercial Energy Efficiency Requirements.

The following spray polyurethane foam product(s) has/have been installed:

- | | | |
|-----------------------|-----------------------|-------------------------|
| UPC 500 Open-Cell | UPC 2.0 HFO | UPC 2.0 HFC Closed-Cell |
| UPC 500 Max Open-Cell | UPC 2.0 HFO Max | UPC 2.0 HFC Max |
| UPC 500 OCX Open-Cell | UPC 2.0 High-Lift HFO | UPC 2.0 HFC High-Lift |

Please consult International Building Code, Chapter 26 – Plastic and International Residential Code (IRC) R316 Foam Plastics for specific requirements. The spray polyurethane foam insulation system(s) has/have been installed in accordance with manufacturer’s processing guidelines to provide a thermal resistance of:

Area Insulated	Aged R-Value	Thickness
Attic Area	R- at	inches
Sloped Ceilings	R- at	inches
Walls (location)	R- at	inches
Walls (location)	R- at	inches
Floors (over an unheated crawl space)	R- at	inches
Crawl Space Perimeter	R- at	inches
Basement Walls	R- at	inches

*Nominal thicknesses are representative of field, spray-applied foam material.

Jobsite Address: _____ Date of Installation: _____

Building Contractor: _____

Insulation Contractor: _____

Insulation Contractor Phone: (_____) _____

Installed by: _____

DO NOT REMOVE

Post near electrical panel.

UNIVERSAL POLYMERS CORPORATION
A Division of General Coatings Manufacturing Corporation

