

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: 90-15472
Product Name: UPC 2.0 Premium HFO
Revision Date: Jul 30, 2025 **Date Printed:** Jul 30, 2025 **Supersedes Date:** N.A.
Version: 1.0
Manufacturer's Name: Universal Polymers Corporation
Address: 8550 W. Desert Inn Rd., Suite 102-380, Las Vegas, NV, US, 89117
Emergency Phone: Chemtrec: 800-424-9300 (account: CCN1217) OR International: 703-527-3887 (account: CCN1217)
Information Phone Number: (682) 503-8069
Fax: (682) 334-7067
Product/Recommended Uses: For Further Information, Refer to the Product Technical Data Sheet.

SECTION 2) HAZARDS IDENTIFICATION

Classification

Acute toxicity Inhalation Vapor - Category 4
Acute toxicity Oral - Category 5
Carcinogenicity - Category 1B
Eye Irritation - Category 2
Germ Cell Mutagenicity - Category 2
Skin Irritation - Category 2
Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Health

H332 - Harmful if inhaled.
H303 - May be harmful if swallowed.
H350 - May cause cancer.
H319 - Causes serious eye irritation.
H341 - Suspected of causing genetic defects.
H315 - Causes skin irritation.

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 - Use only outdoors or in a well-ventilated area.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves, protective clothing, eye protection/face protection.
P264 - Wash thoroughly after handling.

Precautionary Statements - Response

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER/doctor if you feel unwell.
P308 + P313 - IF exposed or concerned: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P302 + P352 - IF ON SKIN: Wash with plenty of water.
P321 - Specific treatment (see section 4 on this SDS).
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P362 + P364 - Take off contaminated clothing. And wash it before reuse.

Precautionary Statements - Storage

P405 - Store locked up..

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0102687-65-0	1-PROPENE, 1-CHLORO-3,3,3-TRIFLUORO-, (1E)-	1- 30%
0013674-84-5	2-PROPANOL, 1-CHLORO-. PHOSPHATE (3:1)	1 - 15%
TRADE SECRET	TERTIARY AMINE	1% - 5%
0000107-21-1	ETHYLENE GLYCOL	0.5% - 5%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor.

If exposed/feel unwell/concerned: Call a POISON CENTER/doctor.

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

Get Medical advice/attention if you feel unwell.

If exposed/If you feel unwell/If concerned: Call a POISON CENTER/doctor.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Gently blot or brush away excess product. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before re-use or discard.

IF exposed or concerned: Get medical advice/attention.

Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes.

If skin irritation occurs: Get medical advice/attention.

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts).

Wash contaminated clothing before re-use or discard.

If exposed/If you feel unwell/If concerned: Get medical advice/attention

Eye Contact

Avoid direct contact. Wear chemical protective gloves, if necessary.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open.

Remove contact lenses, if present and easy to do.

Continue rinsing for a duration of 15-20 minutes.

Take care not to rinse contaminated water into the unaffected eye or onto the face.

If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position.

IF exposed or concerned: Get medical advice/attention.

Rinse mouth.

If exposed/If you feel unwell/If concerned: Call a POISON CENTER/doctor.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam.

Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

Large Fire : Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards Arising from the Chemical

Heated containers may build up pressure and rupture violently. Therefore, use cold water to cool fire-exposed containers.

Fire will produce irritating and toxic gases.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Isolate immediate hazard area and keep unauthorized personnel out.

Stop spill/release if it can be done safely.

Move undamaged containers from immediate hazard area if it can be done safely.

Cool containers with flooding quantities of water until well after fire is out.

Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear NIOSH approved self-contained breathing apparatus in positive pressure mode with full-face piece. Boots, gloves (neoprene), goggles, and full protective clothing are also required.

Care should always be exercised in dust/mist areas.

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Stay uphill and/or upstream.

Ventilate closed spaces before entering.

Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Evacuate and isolate hazard area and keep unauthorized personnel away.

Personal Precautions

Avoid breathing vapors. Avoid contact with skin, eyes or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Do not breathe vapor or mist.

Do not get on skin, eyes or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Stop spill/release if it can be done safely.

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Contain and absorb large spillages onto an inert, non-flammable adsorbent carrier (such as earth or sand). Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spillage area clean with liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable.

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal.

Ventilate area after clean-up is complete.

Protective Equipment

Appropriate dust or face mask to eliminate breathing foam dust particulates.

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored

All containers must be properly labelled.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Use only with adequate ventilation to control air contaminants to their exposure limits.

The use of local ventilation is recommended to control emissions near the source.

Report ventilation failures immediately.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

Do not cut, drill, grind, weld, or perform similar operations on or near containers. Do not pressurize containers to empty them. Ground all structures, transfer containers and equipment to conform to the national electrical code. Use procedures that prevent static electrical sparks. Static electricity may accumulate and create a fire hazard.

Ideal storage temperature is 50-75°F.

Store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities.

Keep containers securely sealed when not in use.

Containers that have been opened must be carefully resealed to prevent leakage.

Indoor storage should meet OSHA standards and appropriate fire codes.

Empty containers retain residue and may be dangerous.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

If additional protection is needed for entire face, use in combination with a face shield.

Wear eye protection with side shields or goggles.

Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Depending on conditions of use, additional protection may be required such as apron, arm covers, or full body suit.

Wash contaminated clothing before re-wearing.

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves.

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity.

Always seek advice from glove suppliers.

Contaminated gloves should be replaced.

Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber.

Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If airborne concentrations exceed or are expected to exceed the TLV, use MSHA/NIOSH approved positive pressure supplied pressure supplied air respiratory with a full face piece or an air supplied hood. For emergencies, use a positive pressure self-contained breathing apparatus.

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed.

Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	COSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)
1-PROPENE, 1-CHLORO-3,3,3-TRIFLUORO-, (1E)-								
ETHYLENE GLYCOL								

Chemical Name	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
1-PROPENE, 1-CHLORO-3,3,3-TRIFLUORO-, (1E)-						2.5		
ETHYLENE GLYCOL					25 (v)		50 (v)	10 (I,H)

(IFV) - Inhalable fraction and vapor

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	10.00 lb/gal
Specific Gravity	1.20
VOC Regulatory	0.00 lb/gal
VOC Part A & B Combined	N.A.
Appearance	Light brown liquid
Odor Threshold	N.A.
Odor Description	Slight ethereal
pH	N.A.
Water Solubility	N.A.
Flammability	N/A
Flash Point Symbol	N.A.
Flash Point	149 °C
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.

Vapor Pressure	N.A.
Vapor Density	Heavier than air
Freezing Point	N.A.
Melting Point	N.A.
Low Boiling Point	19 °C
High Boiling Point	N.A.
Auto Ignition Temp	N.A.
Decomposition Pt	N.A.
Evaporation Rate	Slower than ether
Coefficient Water/Oil	N.A.

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Material is stable at standard temperature and pressure.

Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid high temperatures, heated material will build pressure and may rupture the container violently.

Avoid heat, sparks, flame and contact with incompatible materials

Incompatible Materials

Strong mineral acids and strong alkalis will seriously degrade material. Heat may be involved.

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Highly unlikely under normal industrial use. Under extreme heat and fire, carbon monoxide, carbon dioxide.

Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Causes skin irritation

Serious Eye Damage/Irritation

Causes serious eye irritation

Respiratory/Skin Sensitization

No data available.

Carcinogenicity

May cause cancer.

Germ Cell Mutagenicity

Suspected of causing genetic defects.

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

No data available.

Specific Target Organ Toxicity - Repeated Exposure

0000107-21-1 ETHYLENE GLYCOL

The substance may cause effects on kidneys as a result of repeated ingestion.

Aspiration Hazard

Based on available data, the classification criteria are not met.

Acute Toxicity

Harmful if inhaled.

May be harmful if swallowed.

Chronic Exposure

Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0000107-21-1 ETHYLENE GLYCOL

The substance can be absorbed into the body by inhalation, through the skin and by ingestion.

Potential Health Effects - Miscellaneous

No data available.

0000107-21-1 ETHYLENE GLYCOL

LD50 (oral, rat): 5.89 g/kg; 8.54 g/kg; 13.0 g/kg (5)

LD50 (oral, mouse): 7.5 g/kg; 15.28 g/kg (5,6)

LD50 (oral, guinea pig): 6.6 g/kg; 11.0 g/kg (5)

LD50 (oral, rabbit): 5.0 g/kg (5)

LD50 (dermal, rabbit): 9.5 g/kg (6)

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

No data available.

Persistence and Degradability

0000107-21-1 ETHYLENE GLYCOL

Readily biodegradable.

Bioaccumulative Potential

0000107-21-1 ETHYLENE GLYCOL

No potential for bioaccumulation.

Mobility in Soil

0000107-21-1 ETHYLENE GLYCOL

Adsorption to solid soil phase is not expected. Ethylene glycol will preferentially be distributed into the compartment water.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000107-21-1 ETHYLENE GLYCOL

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste.

Waste management should be in full compliance with national, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Not regulated

IMDG Information

Not regulated

IATA Information

Not regulated

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0102687-65-0	1-PROPENE, 1 CHLORO 3,3,3-TRIFLUORO-, (1E)-	1% - 30%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA)
0013674-84-5	TRIFLUORO-, (1E)-2-PROPANOL, 1-CHLORO-	1% - 15%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000107-21-1	PHOSPHATE (3:1) ETHYLENE GLYCOL	0.5% - 5%	SARA313, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, OC_HAPS, VOC, TSCA - Toxic Substances Control Act (TSCA), California Proposition 65

SECTION 16) OTHER INFORMATION

OTHER INFORMATION

Note: As per GHS, category 1 is the greatest level of hazard within each class.

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; ANSI - American National Standards Institute; CA Prop65 - California Proposition 65; Canadian TDG - Canadian Transportation of Dangerous Goods; CAS - Chemical Abstract Service; Chemtrec - Chemical Transportation Emergency Center (US); CHIP - Chemical Hazard Information and Packaging; DSL - Domestic Substances List; EC - Equivalent Concentration; EH40 (UK) - HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA - Emergency Planning and Community Right-To-Know Act; ESL - Effects screening levels; HMIS - Hazardous Material Information Service; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA - Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA (Title III) - Superfund Amendments and Reauthorization Act; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self-Contained Breathing Apparatus; STEL - Short Term Exposure Limit; TCEQ - Texas Commission on Environmental Quality; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time Weighted Value; US DOT - US Department of Transportation; WHMIS - Workplace Hazardous Materials Information System.

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL - Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA - Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT - US Department of Transportation.

Version 1.0:

Revision Date: Jul 30, 2025

Version 1.0

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.